

PRODUCT NAME/VISCOSITIES: TRIDENT LONGLIFE 5w40

DATA SHEET NO: 6124

DESCRIPTION:

A high performance fully synthetic petrol and diesel engine oil suitable for latest technology petrol and diesel engines.

APPLICATION:

Suitable for use in petrol and diesel engines meeting Euro IV & V emissions standards, with or without diesel particulate filters.

Particularly recommended for use in vehicles using variable service intervals and other vehicles that require a fuel-efficient lubricant.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection
- A mid SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)

PERFORMANCE PROFILE:

- ACEA C3
- API SN, CF
- Meets the requirements of MB 229.3, MB 229.51, VW 502 00, 505 01, Ford M2C917-A, BMW Longlife-04, Porsche A40, GM dexos 2, Fiat 9.55535-S2

TYPICAL CHARACTERISTICS:

SAE Grade	SAE 5w	′ 40
Specific Gravity @ 15°C	0.850	
Kinematic Viscosity @ 100°C		14.4cSt
Kinematic Viscosity @ 40°C	86cSt	
Viscosity Index	174	
Pour point °C		-39
Flashpoint °C		>200
Cold Crank Viscosity @ -30°C		6,600Cp max

Millers Oils Limited Brighouse West Yorkshire HD6 3DP Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email <u>enquiries@millersoils.co.uk</u> www.millersoils.co.uk





HEALTH AND SAFETY:

Health and Safety Data Sheet 6124 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited Brighouse West Yorkshire HD6 3DP Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email <u>enquiries@millersoils.co.uk</u> www.millersoils.co.uk

