



Quality is in our nature

Passenger car engine oils - Fully Synthetic

# Eurol Synergy 0W-40

Fully synthetic fuel economy long-life motor oil MB 229.5

## Beschreibung

Eurol Synergy 0W-40 is a fully synthetic motor oil for use in passenger cars and light duty commercial vehicles. This oil can be used in cars with turbo charged engines, catalytic converters and direct fuel injection diesel engines.

and can be used for an intensive and prolonged use.

Eurol Synergy 0W-40 provides an extremely rapid and stable lubricant film at the cold start and maintains this film at high operating temperatures

Next to this, this oil offers an extremely high oxidation stability and wear protection. Both engine and oil stay clean, even after prolonged drain intervals (up to 30.000 km).

Eurol Synergy 0W-40 offers extra fuel saving properties and can be mixed with both synthetic and mineral motor oils, although especially for this oil, mixing with other oils will not benefit the outstanding quality of the products.

Eurol Synergy 0W-40 meets the MB 229.5 specification

## Specifications

<u>Approved</u>	Ford WSS-M2C937-A
<b>BMW Longlife-01</b>	VW 505.00
<u>Performance level</u>	<u>Recommended for use</u>
API SN/CF	Fiat 9.55535-Z2
ACEA A3/B4	Fiat 9.55535-N2
VW 502.00	Fiat 9.55535-M2
MB 229.5	Fiat 9.55535-H2
MB 229.3	
Porsche A40	
Renault RN0710	
Renault RN0700	

## Physikalische Eigenschaften

Farbe	Braun	
Dichte bei 20°C	0.8407 kg/L	ASTM D 1298
Viskosität, kinematisch bei 40°C	73.5 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	13.1 cSt	ASTM D 445
Viscosity Index	182	ASTM D 2270
Viskosität, dynamisch (CCS)	5260 cP	ASTM D 2602
Sulphated ash	1.09 wt%	ASTM D 874
Flammpunkt	207 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Available in 1L - 5L - 20L - 60L - 210L - IBC - BULK

E100064

Version 1.0, 03-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com