





Passenger car engine oils - Fully Synthetic

# Eurol Syndura 5W-40

Fully synthetic oil for gasoline and diesel engines, with or without turbo

### Beschreibung

Eurol Syndura 5W-40 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Syndura 5W-40 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Syndura 5W-40 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Syndura 5W-40 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

#### **Specifications**

Approved	Renault RN0710
MB-Approval 229.5	Renault RN0700
Performance level	GM-LL-B-025
API SN/CF	Fiat 9.55535-M2
ACEA A3/B4	Fiat 9.55535-H2
VW 502.00	VW 505.00
MB 226.5	
BMW Longlife-01	
PSA B71 2296 / PSA B71	
2293	
Porsche A40	

#### Physikalische Eigenschaften

Farbe	Braun	
Dichte bei 20°C	0.8524 kg/L	ASTM D 1298
Viskosität, kinematisch bei 40°C	86.2 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	14.9 cSt	ASTM D 445
Viscosity Index	182	ASTM D 2270
Viskosität, dynamisch (CCS)	5400 cP	ASTM D 2602
Flammpunkt	203 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

## Available in 5L - 200L - 210L

E100084 Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.