



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Super Lite 5W-50

Fully synthetic oil for gasoline and diesel engines, with or without turbo

Beschreibung

Eurol Super Lite 5W-50 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Super Lite 5W-50 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Super Lite 5W-50 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Super Lite 5W-50 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Specifications

Performance level
API SN/CF
Recommended for use
ACEA A3/B4
VW 502.00
MB 229.3
Renault RN0710
Renault RN0700
VW 505.00

Physikalische Eigenschaften

Farbe	Braun	
Dichte bei 20°C	0.8526 kg/L	ASTM D 1298
Viskosität, kinematisch bei 40°C	119.1 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	19.6 cSt	ASTM D 445
Viscosity Index	187	ASTM D 2270
Viskosität, dynamisch (CCS)	6106 cP	ASTM D 2602
Base number	10.4 mg KOH/g	ASTM D 2896
Sulphated ash	1.26 wt%	ASTM D 874
Flammpunkt	203 °C	ASTM D 93
Pour point	-39 ℃	ASTM D 97

Available in 1L - 4L - 5L - 20L - 60L - 200L - 210L - IBC - BULK

E100093 Version 1.0, 03-03-2016