

PRODUCT DATA SHEET

Trident





DATA SHEET NO:

7996

PRODUCT NAME/VISCOSITIES:

TRIDENT LONGLIFE V 5w30

DESCRIPTION:

A high performance fully synthetic petrol and diesel engine oil suitable for petrol and diesel engines.

APPLICATION:

Suitable for use in petrol and diesel engines meeting the latest European emissions standards, with or without diesel particulate filters. For use in 504 507 applications in vehicles in and out of warranty.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity is maintained even under the most severe operating conditions thereby ensuring maximum engine protection.
- A mid SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)

PERFORMANCE PROFILE:

- VW 504.00 507.00
- Porsche C30

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 5w30
Specific Gravity @ 15°C 0.857
Kinematic Viscosity @ 100°C 12.3cSt
Kinematic Viscosity @ 40°C 76.50cSt
Viscosity Index 159
Pour point °C -30
Flashpoint °C >200

Cold Crank Viscosity @ -30°C 6,600cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 7996 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited Brighouse West Yorkshire HD6 3DP Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email enquiries@millersoils.co.uk www.millersoils.co.uk









For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited Brighouse West Yorkshire HD6 3DP Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email enquiries@millersoils.co.uk www.millersoils.co.uk



