ATF BMV

Last updated: 07/02/2018 2:29 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
ATFBMV004	4L	4
ATFBMV020	20L	
ATFBMV060	60L	

PRODUCT BENEFITS

ATF BMV is a highly advanced, low viscosity, full synthetic, multi vehicle automatic transmission fluid designed for the latest generation of European, Asian and US sourced automatic transmissions. It utilises the latest additive technology for optimum performance, durability and shift quality in modern multi-speed automatic transmissions.

APPLICATIONS

ATF BMV is suitable for long drain use in 5 + speed automatic transmissions in passenger cars, 4WD's and light duty commercial vehicles.

ATF BMV may be used in ZF 6, 8 and 9 speed automatic transmissions where Lifeguard 6, 8 & 9 is recommended in vehicles such as –



ATF BMV can also be used in Mercedes Benz and Chrysler vehicles where MB 236.10, MB 236.11, MB 236.12, MB 236.13, and MB 236.14 are specified in Mercedes Benz 5 speed W5A 580 / NAG1, NAG2V Sport Transmissions and 7 G-Tronic models W7A 700 / NAG2.

Note: Not for use in 722.9, NAG2FE applications or where MB 236.15 or MB 236.16 is specified.

ATF BMV may be used in Ford Falcon BF-FG series 6 speed automatic transmissions as well as in the 6R80 6 speed transmissions used in Ford PX Ranger and Mazda BT50 models. It can also be used in BMW X5, 5/6 and 7 series, Aston Martin DBS/DB9, Jaguar XK8, XKR, S Type and in Chrysler 300 series, Jeep Grand Cherokee and Cherokee series that use ZF 8 and 9 speed automatic transmissions as well as many other vehicles.

REPLACES OEM PART NUMBERS

- Audi TL 52533 (G052 533), G055 005 A1/A2/A6, G 060 162 A1/A2/A6 ATF
- Bentley PY112995PA
- BMW PY112995PA, 8322 0142516, 8322 2152426
- Chrysler Part No. 68157995AA, 68218925GA
- Citroen Z000169756
- Hyundai Oil No. 040000C90SG
- Jaguar Part Number 02JDE 26444, JLM20238, Fluid 8432
- Land Rover Part No. LR023288, TYK500050
- Maserati 231603
- Mercedes Benz A0019892203
- Porsche 999.917.547.00
- VW Part No. G 060 162 A1/A2/A6 ATF, G055 005 A1/A2/A6, VW TL 52533 (G052 533)
- ZF No. S671 090 255 (Lifeguard 6), ZF No. S671 090 (Lifeguard 8), ZF No. AA01.500.001 (Lifeguard 9)

ATF BMV is also suitable for power steering systems requiring a low viscosity automatic transmission fluid as well as rotary vane and screw type compressors and hydraulic systems requiring an ISO 32 oil.

Please Note: Not for use in Dual Clutch Transmissions (DCT) or Continuously Variable Transmissions (CVT). Please refer to Penrite Recommendation Guide.



PRODUCT BENEFITS

- One product for multiple applications reduces misapplication
- · Designed to meet friction requirements for low viscosity fluids
- · Extends transmission life through superior wear protection
- Improved power transfer, fuel economy & reduced deposit formation
- Extended service life utilising synthetic base oils and a shear stable formulation
- · Maximises equipment life by maintaining wear protection and oil film strength throughout the drain interval

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- Ford MERCON® LV
- Ford MERCON® SP
- Ford WSS-M2C919-D
- Ford WSS-M2C938-A
- MB 236.10

- MB 236.11
- MB 236.12
- MB 236.13
- MB 236.14

SUITABLE FOR USE WHERE SPECIFICATIONS BELOW ARE REQUIRED (FOR OUT OF WARRANTY SERVICE)

- Audi G 060 162 A1
- Audi G 060 162 A2
- Audi G 060 162 A6
- Audi G055 005 A1
- Audi G055 005 A1
 Audi G055 005 A2
- Audi G055 005 A6
- Audi TL 52533
- Bentley PY112995PA
- BMW 8322 0142516
- BMW 8322 2152426
- BMW PY112995PA
- Chrysler 68157995AA
- Chrysler 68218925GA
- Citroen Z000169756
- Ford MERCON® LV
- Ford MERCON® SP
- Ford WSS-M2C919-D
- Ford WSS-M2C938-A
- Hyundai 040000C90SG
- Maserati 231603
- MB 236.10
- MB 236.11
- MB 236.12
- MB 236.13MB 236.14
- Mercedes Benz A0019892203
- Porsche 999.917.547.00
- VW G 060 162 A1
- VW G 060 162 A2
- VW G 060 162 A6
- VW G055 005 A1
- VW G055 005 A2
- VW G055 005 A6
- VW TL 52533 (G052 533)
- ZF AA01.500.001 (Lifeguard 9)
- ZF Lifeguard Fluid 6
- ZF Lifeguard Fluid 8
- ZF Lifeguard Fluid 9
- ZF S671 090 (Lifeguard 8)
- ZF S671 090 255 (Lifeguard 6)

Website: www.penriteoil.com.a Email: penrite@penriteoil.com



TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.845
Viscosity, Kinematic, cSt at 40°C	29.0
Viscosity, Kinematic, cSt at 100°C	6.1
Viscosity Index	161
Viscosity, Brookfield, cSt @ -40°	13,702
Phosphorus, Mass %	0017

Email: penrite@penriteoil.com