TRANS GEAR 75W-80 (Semi Syn.)

Last updated: 30/01/2018 12:30 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
TG7580001	1L	6
TG75800025	2.5L	4
TG7580020	20L	
TG7580060	60L	

PRODUCT BENEFITS

Trans Gear 75W-80 is a premium performance, semi-synthetic manual gearbox oil. It uses the latest technology, purpose designed additives for long service life and contains a unique viscosity modifier for enhanced low temperature performance. It meets the performance requirements of API GL-4 Plus as well as many other manufacturers requirements.

VISCOSITY

• 75W-80

BASE OIL

Semi Synthetic

USED IN THE FOLLOWING APPLICATIONS

- Manual Gearboxes
- Transfer Cases
- Transaxles

ADDITIONAL PRODUCT INFORMATION

· Click here to view Gear Oil flyer

APPLICATION

Trans Gear 75W-80 is suitable for manual gearboxes, transfer cases and transaxles in passenger vehicles, 4WDs & light commercial. It is suitable for use in some ZF truck manual gearboxes and is also suitable for use in BTR T-5 gearboxes.

Trans Gear 75W-80 has an advanced, non-aggressive chemistry that makes it an ideal replacement for synthetic 10W-30 or 5W-40 engine oils used in manual gearboxes as well as in motorcycle gear boxes.

Trans Gear 75W-80 may also be used in some older style manual gearboxes that require automatic transmission fluids, and in vehicles that are suffering from shift quality problems with higher viscosity fluids.

PRODUCT BENEFITS

- · Smooth shift feel for the life of the oil
- · Reduces harmful deposits
- Excellent wear protection
- · Contains synthetic base oils for longer life
- · Will not harm brass or bronze
- · Compatible with synchro materials

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- API GL-4
- API GL-4 Plus
- Chrysler MS-9224
- Honda MTF 7289

- Land Rover MTF 94
- MB 235.10
- ZF TE-ML 02D





TYPICAL DATA

Colour	Brown
Density at 15°C, kg/L	0.865
Viscosity, Kinematic, cSt at 40°C	56
Viscosity, Kinematic, cSt at 100°C	10.6
Viscosity Index	183
Viscosity, Brookfield, cSt @ -40°	11,800
Zinc, Mass %	0.139
Pour Point, °C	-51

Email: penrite@penriteoil.com