



PENRITE



85% REDUCTION
IN LANDFILL
WASTE

PRO GEAR 75W-85 (Full Syn.)

Last updated: 30/01/2018 12:30 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
PROG7585001	1L	6
PROG75850025	2.5L	4
PROG7585020	20L	
PROG7585060	60L	

PRODUCT BENEFITS

Pro Gear 75W-85 is a premium full synthetic manual gearbox oil manufactured from a blend of carefully selected synthetic base oils. It uses the latest technology, purpose designed additives for long service life and excellent load carrying capacity. It contains a unique viscosity modifier for stay-in-grade performance for the life of the drain. It meets the performance requirements of API GL-4 Plus as well as many manufacturer requirements.

VISCOSITY

- 75W-85

BASE OIL

- Full Synthetic

USED IN THE FOLLOWING APPLICATIONS:

- Manual Gearboxes
- Transaxles
- Transfer Cases

CAN BE USED WHERE THE FOLLOWING SAE VISCOSITIES ARE RECOMMENDED

- SAE 80
- 80W-85

ADDITIONAL PRODUCT INFORMATION

- [Click here](#) to view Gear Oil flyer

APPLICATION

Pro Gear 75W-85 is suitable for manual gearboxes, transfer cases and transaxles in passenger cars, 4WDs and trucks that specify the use of SAE 75W-85 oils. It may also be used in place of an SAE 80 or SAE 80W-85 gearbox oil, especially to improve cold shift problems, where the lower start up viscosity will provide an easier shift.

Pro Gear 75W-85 is also ideal in vehicles that are operating in highly loaded conditions such as in competition or when towing. It may also be used in manual gearboxes and transaxles that require a SAE 75W-80.

Pro Gear 75W-85 is recommended for use in Aisin 6 speed manual gearboxes used by Toyota and in Holden Commodore VE V6 and is also suitable for use in GM NV3500 and NV4500 manual gearboxes.

NOTE: This product is not suitable for use in differentials requiring an AP GL-5 specification. For these applications, please use Penrite Pro Gear GL-5 75W-85

PRODUCT BENEFITS

- Smooth shift feel for the life of the oil
- Reducing harmful deposits
- Will not harm brass or bronze
- Compatible with synchro materials
- Excellent wear protection
- Contains synthetic base oils for longer life





PENRITE



**85% REDUCTION
IN LANDFILL
WASTE**

INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- API GL-4
- API GL-4 Plus
- BTR 5M-42
- Chrysler MS-9224
- Ford M2C200-C
- GM 12346190
- GM HN 1820
- GM HN 1855
- GM HN 2276
- MAN 341
- MB 235.4.
- MB 235.5.
- Opel 040 0063
- Opel 040 1067
- ZF TE-ML 01
- ZF TE-ML 02
- ZF TE-ML 08

TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.873
Viscosity, Kinematic, cSt at 40°C	77
Viscosity, Kinematic, cSt at 100°C	12.0
Viscosity Index	152
Viscosity, Brookfield, cSt @ -40°	111,000
Zinc, Mass %	0.139