

Q8 Formula Exclusive C3 0W-30

Description

Ultra High Performance Low SAPS SAE 0W-30 Synthetic Engine Oil for Euro 5 and 6 diesel engines requiring ACEA C3

Application

- Engine oil for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 6 & Euro 5 engines requiring Low SAPS engine oil.

Specifications

- ACEA C3

Benefits

- Low SAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.
- Excellent bio-diesel compatibility.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 0W-30
Density, 15 °C	D 4052	kg/m ³	843
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.6
Kinematic Viscosity, 40 °C	D 445	mm ² /s	64.0
Viscosity Index	D 2270	-	180
Apparent Viscosity, -35 °C	D 5293	mPa.s	5700
Pour Point	D 97	°C	-42
Flash Point	D 92	°C	205
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>-3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

